

Appl. No. 09/965,998  
Amdt. dated November 30, 2005  
Reply to final Office Action of August 30, 2005

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Withdrawn) A method comprising:  
storing operating system drivers for at least two different types of operating systems on a read only memory (ROM) within the computer system; and  
copying at least one of the operating system drivers from a virtual disk drive of the computer system during the operating system installation.
2. (Currently amended) A method comprising:  
~~of~~ providing operating system drivers during an operating system installation on a computer system by the method comprising:  
storing the operating system drivers on a read only memory (ROM) within the computer system;  
copying at least one of the operating system drivers from a virtual disk drive of the computer system during the operating system installation by:  
invoking basic input output system (BIOS) routines;  
~~showing~~ identifying the operating system drivers residing on the ROM as files stored on the virtual disk drive by the BIOS routines; and  
having only operating system drivers operable with the operating system to be installed available for copying from the virtual disk drive by identifying ~~showing~~ only the operating system drivers operable with the operating system to

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

be installed as files stored on the virtual disk drive by the BIOS routines.

3. (Previously presented) The method of providing operating system drivers as defined in claim 2 further comprising:

requesting disk services to the virtual disk drive by:

invoking interrupt 13h BIOS routines directed to the virtual disk drive; and

returning a file name for at least one of the operating system drivers by the interrupt 13h BIOS routines as if the operating system drivers resided on the virtual disk drive.

4. (Withdrawn) The method of providing operating system drivers as defined in claim 1 wherein storing the operating system drivers on the ROM within the computer system further comprises storing the operating system drivers on the ROM along with a basic input output system (BIOS).

5. (Withdrawn) The method as defined in claim 1 wherein storing operating system drivers on the ROM within the computer further comprises:

storing on the ROM a first set of operating system drivers operable with a first operating system; and

storing on the ROM a second set of operating system drivers operable with a second operating system.

6. (Withdrawn) The method as defined in claim 5 further comprising having only operating system drivers operable with the operating system to be installed available for copying from the virtual disk drive.

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

7. (Currently amended) A method comprising:  
~~of providing operating system drivers during an operating system~~  
~~installation on a computer system by, the method comprising:~~  
storing the operating system drivers on a read only memory (ROM)  
within the computer system by:  
storing on the ROM a first set of operating system drivers  
operable with a first operating system; and  
storing on the ROM a second set of operating system drivers  
operable with a second operating system;  
copying at least one of the operating system drivers from a virtual  
disk drive of the computer system during the operating  
system installation; and  
having only operating system drivers operable with the operating  
system to be installed available for copying from the virtual  
disk drive by ~~showing-identifying~~ only the operating system  
drivers operable with the operating system to be installed as  
files stored on the virtual disk drive by the BIOS routines.
8. (Currently amended) The method of providing operating system drivers as  
defined in claim 7 wherein ~~showing-identifying~~ the operating system drivers as  
files stored on the virtual disk drive further comprises:  
requesting disk services to a disk drive name that does not physically  
reside in the computer system by:  
invoking interrupt 13h BIOS routines directed to the disk drive name that  
does not physically reside in the computer system;  
returning a file name for operable operating system drivers by the interrupt  
13h BIOS services as if the operating system drivers resided on the  
disk drive name that does not physically reside in the computer  
system.

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

9. (Withdrawn) A computer system comprising:  
a CPU;  
a main memory array coupled to the CPU;  
an expansion bus coupled to the CPU; and  
a read only memory (ROM) array coupled to the expansion bus, wherein  
the ROM array stores operating system drivers;  
wherein the computer system makes the operating system drivers appear  
to reside on a virtual floppy drive for copying during installation of an  
operating system for the computer system, and wherein the  
computer system loads the operating system drivers during booting  
of the operating from locations other than the ROM.
10. (Withdrawn) The computer system as defined in claim 9 wherein the ROM  
array also stores basic input output system (BIOS) firmware.
11. (Withdrawn) The computer system as defined in claim 10 wherein the  
BIOS firmware, when invoked for disk services, makes the operating system  
drivers appear to reside on the virtual floppy drive.
12. (Withdrawn) The computer system as defined in claim 9 further  
comprising:  
said ROM array stores a first set of operating system drivers for a first  
operating system;  
said ROM array stores a second set of operating system drivers for a  
second operating system; and  
wherein the computer system makes only one of the first and second set  
of operating system drivers available for copying from the virtual  
floppy drive during installation of the operating system for the  
computer system.

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

13. (Withdrawn) A method comprising:  
storing operating system drivers on a read only memory (ROM);  
informing a basic input output system (BIOS) of an operating system type to be installed;  
making available during the installation of the operating system the operating system drivers stored on the ROM appropriate for the operating system type to be installed;  
installing the operating system;  
copying at the appropriate time during the installation of the operating system at least one of the operating system drivers from a virtual floppy drive; and then  
booting the installed operating system.
14. (Withdrawn) The method as defined in claim 13 wherein storing operating system drivers on the ROM further comprises:  
storing a first set of operating system drivers operable with a first operating system; and  
storing a second set of operating system drivers operable with a second operating system.
15. (Withdrawn) The method as defined in claim 14 wherein informing the BIOS of the operating system type to be installed further comprises:  
selecting the operating system type to be installed on a BIOS setup screen; and  
setting an environment variable in a non-volatile random access memory (RAM) based on the selecting step that indicates the operating system type to be installed.

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

16. (Withdrawn) The method as defined in claim 15 wherein making available the operating system drivers stored on the ROM further comprises:

using BIOS programs to access the operating system drivers stored on the ROM;

referring, by the BIOS programs, to the environment variable in non-volatile RAM; and

making one of the first and second set of operating system drivers available on the virtual floppy drive by the BIOS program based on a state of the environment variable in non-volatile RAM.

17. (Currently amended) A read only memory (ROM) device comprising:

a basic input output system (BIOS) program;

a set of hardware drivers; and

wherein the BIOS program, when executed by a microprocessor, makes the set of hardware drivers available for copying during installation of an operating system by ~~showing~~identifying the hardware drivers on the ROM as files on a virtual disk drive;

wherein the hardware drivers are made available for copying from the virtual disk drive by ~~showing~~identifying only the hardware drivers operable with the operating system to be installed.

18. (Previously presented) The ROM device as defined in claim 17 wherein the set of hardware drivers further comprises:

a first set of hardware drivers for use with a first type operating system;

a second set of hardware drivers for use with a second type operating system; and

wherein the BIOS program makes only the first set of hardware drivers available during installation of the first type operating system, and wherein the BIOS program makes only the second set of hardware drivers available during installation of the second type operating system.

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

19. (Withdrawn) A method of providing operating system drivers during an operating system installation on a computer system, the method comprising:
- storing a first set of operating system drivers operable with a first operating system in a read only memory (ROM) of the computer system;
  - storing a second set of operating system drivers operable with a second operating system in the ROM; and
  - copying at least one of the operating system drivers from a virtual disk drive of the computer system during the operating system installation.
20. (Withdrawn) The method of providing operating system drivers as defined in claim 19 further comprising:
- selecting on a basic input output system (BIOS) setup screen one of the first and second sets of operating systems, a selected system, to be installed on the computer system; and
  - having only operating system drivers operable with selected system, selected drivers, available for copying from the virtual drive.
21. (Withdrawn) The method of providing operating system drivers as defined in claim 20 further comprising:
- requesting disk services to a disk drive name that does not physically reside in the computer system by:
  - invoking interrupt 13h BIOS services directed to the disk drive name that does not physically reside in the computer system; and
  - returning file names for the selected drivers by the interrupt 13h BIOS services as if the selected drivers resided on the disk drive name that does not physically reside in the computer system.
22. (Canceled).

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

23. (Currently amended) A computer system comprising:  
a CPU;  
a main memory array coupled to the CPU;  
an expansion bus coupled to the CPU; and  
a read only memory (ROM) coupled to the expansion bus, wherein the ROM stores basic input output system (BIOS) programs;  
wherein the BIOS programs of the ROM show a virtual floppy drive whose contents reside in the random access memory (RAM) area of the virtual address space and whose contents include hardware drivers available for copying during installation of an operating system;  
~~the RAM contains operating system drivers necessary to interface an operating system of the computer system with hardware of the computer system; and~~  
wherein the BIOS programs show the operating system drivers on the RAM as the contents of the virtual floppy drive  
wherein the operating system drivers are made available for copying from the virtual disk drive by ~~showing~~ identifying only the operating system drivers operable with the operating system to be installed.
24. (Currently amended) A computer system comprising:  
a CPU;  
a main memory array coupled to the CPU;  
an expansion bus coupled to the CPU; and  
a read only memory (ROM) coupled to the expansion bus, wherein the ROM stores basic input output system (BIOS) programs;  
wherein the BIOS programs of the ROM show a virtual floppy drive whose contents reside in the ROM area of the virtual address space  
the ROM contains operating system drivers necessary to interface an operating system that is being installed on ~~of~~ the computer system with hardware of the computer system; and



**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

wherein the BIOS programs show the operating system drivers on the ROM as the contents of the virtual floppy drive  
the ROM contains a first set of operating system drivers for use with a first operating system;  
the ROM also contains a second set of operating system drivers for use with a second operating system; and  
wherein the BIOS programs show as contents of the virtual floppy drive only the first set of operating system drivers if the first operating system is to be installed on the computer system, and wherein the BIOS programs are further adapted to show as contents of the virtual floppy drive only the second set of operating system drivers if the second operating system is to be installed on the computer system.

25. (Canceled).

26. (Canceled).

27. (Withdrawn) A method of providing operating system drivers during an operating system installation on a computer system, the method comprising:  
storing a first floppy image having a first set of operating system drivers operable with a first operating system, the first floppy image stored in a read only memory (ROM) of the computer system;  
storing a second floppy image having a second set of operating system drivers operable with a second operating system, the second floppy image stored in the ROM; and  
providing one of the first and second floppy images as a virtual floppy drive during the operating system installation.

**Appl. No. 09/965,998**  
**Amdt. dated November 30, 2005**  
**Reply to final Office Action of August 30, 2005**

28. (Withdrawn) The method of providing operating system drivers as defined in claim 27 further comprising:

selecting on a basic input output system (BIOS) setup screen one of the first and second sets of operating systems, a selected system, to be installed on the computer system; and  
having only the floppy image having operating system drivers operable with selected system, a selected floppy image, available on the virtual floppy drive.

29. (Withdrawn) The method of providing operating system drivers as defined in claim 28 wherein providing one of the first and second floppy images as a virtual floppy drive during the operating system installation further comprising:

requesting disk services to a disk drive name that does not physically reside in the computer system by:  
invoking interrupt 13h BIOS services directed to the disk drive name that does not physically reside in the computer system; and  
returning file names in the selected floppy image by the interrupt 13h BIOS services as if the selected floppy image resided on the disk drive name that does not physically reside in the computer system.